



Passenger car engine oils - Fully Synthetic

Eurol Syndura 5W-40

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Description

Eurol Syndura 5W-40 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Syndura 5W-40 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Syndura 5W-40 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Syndura 5W-40 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Approved

- MB-Approval 229.5
- BMW Longlife-01

Performance level

- API SN/CF
- ACEA A3/B4
- VW 502.00
- MB 226.5
- PSA B71 2296 / PSA B71 2293
- Porsche A40
- Renault RN0710
- Renault RN0700
- VW 505.00

Physical properties

Colour	brown	
Density at 20°C	0.852 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	86.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	182	ASTM D 2270
Viscosity, dynamic (CCS)	5400 cP	ASTM D 5293
Flash point	203 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Article number E100084 Version 5.0, 13-03-2023