



Passenger car engine oils - Fully Synthetic

Eurol Super Lite 5W-20

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Description

Performance level
API SN/CF

Eurol Super Lite 5W-20 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-20 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-20 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-20 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Article number E100089 Version 4.0, 16-07-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.

Physical properties

Colour	amber	
Density at 20°C	0.846 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	47.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.7 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	3880 cP	ASTM D 5293
Base number	8.5 mg	ASTM D 2896
Sulphated ash	0.85 wt%	ASTM D 874
Flash point	209 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97