



Motorcycle oils 4T - Mineral

Eurol 4T Road 20W-50

Mineral motor oil for 4-stroke motorcycles

Description

Eurol 4T Road 20W-50 is a mineral engine oil without friction modifiers and has been especially developed for 4-stroke motorcycles. This oil can also be used in motorcycle transmissions where an API SG oil is prescribed.

Eurol 4T Road 20W-50 is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol 4T Road 20W-50 offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

Eurol 4T Road 20W-50 has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

Performance level

- API SJ
- JASO MA
- JASO MA2

Physical properties

- 11 3 - 11 - 11 - 11 - 11 - 11 - 11		
Colour	brown	
Density at 20°C	0.882 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	147.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	17.4 cSt	ASTM D 445
Viscosity Index	129	ASTM D 2270
Viscosity, dynamic (CCS)	6089 cP	ASTM D 5293
Flash point	219 °C	ASTM D 93
Pour point	-15 °C	ASTM D 97

Article number E100101 Version 1.1, 14-03-2018