



Heavy duty diesel engine oils - low SAPS

Eurol Marathol 10W-40

UHPD motor oil, based on low SAPS technology

Description

Eurol Marathol 10W-40 is an ultra high performance motor oil for commercial vehicles based on the so called 'low SAPS' technology. This means that sulphur, phosphorus and sulphated ash concentrations are reduced radically, to protect the exhaust gas after treatment systems.

Especially Mercedes (228.51) and MAN (M3477) have set up special standards for the oil to meet Euro-4 and Euro-5 emission regulations, including reduced sulphur, phosphorus and sulphated ash concentrations. For this reason, ACEA launched the E6 specification at the end of 2004.

Eurol Marathol 10W-40 has fuel economy properties and because of the special additive technology, both the oil and the engine are kept clean in an unprecedented way. In Euro-4, 5 and Euro-6 engines the harmful exhaust gas emission is reduced.

Eurol Marathol 10W-40 is suitable for extended drain intervals, if allowed by the OEM and depending on working conditions and filtration methods, so it reduces maintenance cost.

Eurol Marathol 10W-40 can also be applied in older trucks with Euro-3 engines, where ACEA E4, Mercedes 228.5 and MAN 3277 are prescribed, as well Renault RXD and DAF HP-2.

Approved

- MB-Approval 228.51
- Volvo VDS-3
- Mack EO-N
- Renault VI RLD-2

Performance level

- API CI-4
- ACEA E6
- ACEA E7
- ACEA E9
- ACEA E8/E11
- MB 226.9
- MAN M 3477
- MAN M 3271-1
- Renault RXD
- Caterpillar ECF-1-A
- CES 20076
- CES 20077
- MTU type 3.1
- Renault RGD
- DAF
- JASO DH-2
- Deutz DQC TTCD, DQC IV-18 LA
- Iveco 18-1804 TLS E6

Physical properties

Colour	brown	
Density at 20°C	0.859 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	98.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.7 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	5466 cP	ASTM D 5293
Base number	10.1 mg	ASTM D 2896
Sulphated ash	0.99 wt%	ASTM D 874
Flash point	232 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Article number E100119
Version 10.0, 19-07-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.