

Eurol Pro Lite 15W-40

Semi-synthetic motor oil for passenger cars and light duty commercial vehicles Article number E100135 Version 1.2 14/04/2025

Product information

Eurol Pro Lite 15W-40 is a semi-synthetic engine oil with universal applicability in gasoline and diesel cars as well as in light commercial vehicles. This oil provides a good lubrication film at both low and high operating temperatures.

Eurol Pro Lite 15W-40 allows the engine to perform under all conditions thanks to its special additive package, meeting both European and American standards. Fuel efficiency and exhaust emission reduction can also be achieved with this product. Due to its unique formulation, this oil has low evaporation, minimizing oil consumption.

Eurol Pro Lite 15W-40 offers excellent protection against wear, foaming, and corrosion. Along with detergent and dispersant properties, this oil keeps the engine clean and in optimal condition.

Due to its high thermal stability, Eurol Pro Lite 15W-40 will maintain its quality level and not thicken.

Eurol Pro Lite 15W-40 is not suitable for use with diesel vehicles equipped with a DPF.

Performance level

- ACEA A3/B4
- API SN/CF
- MB 229.1
- VW 501.01
- VW 505.00

Physical properties

	V 1 (D)	ACTN 0: 1 1
Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.86 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	101.0 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	153	ASTM D 2270
Viscosity, dynamic (CCS)	3,377 cP	ASTM D 5293
Flash Point	202 °C	ASTM D 92
Sulfated Ash	1.3 wt%	ASTM D 874
Pour point	-39 °C	ASTM D 97