

Eurol Nautic L. 25W-40 FCW

4-stroke oil for marine engines

Article number E100138 Version 2.0 14/04/2025

Product information

Eurol Nautic Line 25W-40 FCW is a motor oil that ensures optimal lubrication and protection for 4-stroke inboard and outboard marine engines requiring the FC-W specification.

Eurol Nautic Line 25W-40 FCW meets the NMMA FCW requirements, such as protection against rust and corrosion from (salt)water contact, limited viscosity loss after prolonged use, and excellent protection against wear and sedimentation, especially in the case of fuel dilution*.

*Fuel dilution can occur in engines when the engine runs in neutral for extended periods and unburned fuel leaks into the crankcase. Eurol Nautic Line 25W-40 FCW contains special additives that minimize wear at both low and high speeds.

Thanks to special additives, Eurol Nautic Line 25W-40 FCW maintains its high performance level even after the oil change interval has passed. However, it is always best to ensure timely oil changes.

Performance level

- API SL
- JASO MA
- NMMA FC-W

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.88 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	133.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.0 cSt	ASTM D 445
Viscosity Index	114	ASTM D 2270
Viscosity, dynamic (CCS)	4,713 cP	ASTM D 5293
Flash Point	244 °C	ASTM D 92
Sulfated Ash	0.8 wt%	ASTM D 874
Pour point	-27 °C	ASTM D 97