



Nautic line - Mineral

## Eurol Nautic L. Monograde S30

Mineral motor oil for diesel motors

### Description

Eurol Nautic Line Monograde S was especially developed for lightly to heavily loaded diesel motors with and without turbo and stationary motors. This oil is also suited to diesel motors that run on diesel with a higher sulphur content (up to 0.5%).

Eurol Nautic Line Monograde S has a strong cleansing and protective capacity. This prevents carbon deposits and sedimentation on the pistons, valves and in the combustion chambers.

Eurol Nautic Line Monograde S offers good protection against wear, corrosion, sludge and foaming, while remaining stable even at high temperatures and preventing oil thickening.

### Performance level

- API SF/CF

### Physical properties

Colour	brown	
Density at 20°C	0.881 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	96 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.1 cSt	ASTM D 445
Viscosity Index	101	ASTM D 2270
Base number	10.3 mg	ASTM D 2896
Sulphated ash	1.44 wt%	ASTM D 874
Flash point	218 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

Article number E100141  
Version 4.0, 30-11-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.