



Passenger car engine oils - Fully Synthetic

## Eurol Actence RNT 5W-30

Fully synthetic ACEA C3 and Renault RN17 engine oil

### Description

Eurol ACTENCE RNT 5W-30 is a fully synthetic high performance engine oil for gasoline and diesel vehicles.

Eurol ACTENCE RNT 5W-30 provides maximum protection against rust and corrosion, while the used additive package keeps the engine clean and well lubricated.

Eurol ACTENCE RNT 5W-30 provides an extremely stable lubricant film at the cold start and offers high thermal stability under severe driving operating conditions (motorway and urban traffic). The oil is able to flow and to lubricate critical parts, preventing wear and ensuring engine protection.

Eurol ACTENCE RNT 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid-SAPS" technology).

### Approved

- Renault RN17

### Performance level

- ACEA C3

### Recommended for use

- MB 226.52

### Physical properties

Colour	brown	
Density at 20°C	0.848 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	70.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.3 cSt	ASTM D 445
Viscosity Index	173	ASTM D 2270
Viscosity, dynamic (CCS)	5933 cP	ASTM D 5293
Base number	9.3 mg	ASTM D 2896
Flash point	215 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Article number E100171  
Version 2.0, 17-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.