



Heavy duty diesel engine oils - Fully Synthetic

# **Eurol Geo-Max SA 5W-30**

Fuel economy engine oil developed for road & off road diesel vehicles

# **Description**

Eurol Geo-Max SA 5W-30 is a modern fully synthetic engine oil. It offers fuel economy benefits for naturally aspirated and turbocharged four-stroke diesel engines operating under extreme cicrumstances in various weather conditions, delivering API FA-4 performance.

Eurol Geo-Max SA 5W-30 offers excellent wear, deposit, sludge, and corrosion protection.

Eurol Geo-Max SA 5W-30 is especially effective in applications where particulate filters and other advanced aftertreatment systems are used, prolonging their lifecycle.

By covering a wide range of specifications, Eurol Geo-Max SA 5W-30 enables the fleet-owner to reduce the number of stock keeping units. Eurol Geo-Max SA 5W-30 is also suitable in petrol engines where SAE 5W-30 with API SN performance is specified.

It is not backwards compatible with API CK-4/CJ-4/CI-4 performance.

# **Approved**

• API FA-4/SN

#### Performance level

- DTFR 15C130 (MB 228.61)
- JASO DH-2
- Cummins 20087
- DDC 93K223

## Recommended for use

• Ford WSS-M2C214-B1

## Physical properties

i ilyolodi proportioo		
Colour	brown	
Density at 20°C	0.845 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	58.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.9 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	6058 cP	ASTM D 5293
Flash point	233 °C	ASTM D 93

Article number E100173 Version 3.0, 20-09-2023