



POWERING
PERFORMANCE

PRODUCT DATA SHEET

Eurol SHPD 20W-50 MF TBN 16

Article number E100174 Version 1.2 14/05/2025

Recommended for use

- API CI-4
- Caterpillar ECF-1-A
- Cummins 20071,72,76,77,78
- Deutz DQC III-10
- DTFR 15B110 (MB 228.3)
- Mack EO-N
- MAN M 3275
- Renault RLD/RLD-2
- Volvo VDS-3

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.88 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	167.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	19.0 cSt	ASTM D 445
Viscosity Index	131	ASTM D 2270
Viscosity, dynamic (CCS)	6,100 cP	ASTM D 5293
Flash Point	217 °C	ASTM D 92
Sulfated Ash	2.4 wt%	ASTM D 874
Pour point	-36 °C	ASTM D 97

Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.