

# **Eurol Syntence XT 5W-30**

Fully synthetic long-life motor oil VW 504.00/507.00

Article number E100179 Version 10.0 14/04/2025

#### **Product information**

Eurol Syntence XT 5W-30 is a fully synthetic engine oil for use in gasoline, LPG, and diesel engines, of passenger cars and light commercial vehicles, equipped with exhaust after-treatment systems.

This oil is specifically developed to meet the VW 504.00/507.00 specification. It is prescribed for passenger cars and light commercial vehicles of the VAG group (Volkswagen, Audi, Seat, and Skoda) and is suitable for very long oil change intervals (up to 30,000 km for gasoline and up to 50,000 km for diesel engines). The product is also suitable for cars for which older VW specifications are prescribed such as VW 500.00, 501.01, 502.00, 503.00, 505.00, 505.01, 506.00, and 506.01.

The Eurol Syntence XT 5W-30 also meets the stringent requirements of Porsche C30, MB 229.51, and BMW Longlife-04, making it an excellent all-round product for the major German car brands.

### **Approved**

- BMW Longlife-04
- MB-Approval 229.51
- Porsche C30
- VW 504.00
- VW 507.00

#### Performance level

- ACEA C3
- **API SN**

#### Recommended for use

MB 229.52

## Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.85 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	67.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.6 cSt	ASTM D 445
Viscosity Index	167	ASTM D 2270
Viscosity, dynamic (CCS)	5,724 cP	ASTM D 5293
Flash Point	238 °C	ASTM D 92
Sulfated Ash	0.8 wt%	ASTM D 874
Pour point	-48 °C	ASTM D 97