



Motorcycle oils 4T - Fully Synthetic

## Eurol Sportbike 15W-50

Fully synthetic motor oil for 4-stroke motorcycles

### Description

Eurol Sportbike 15W-50 Full Synthetic is a fully synthetic engine oil and contains a dedicated ester technology to provide extra protection against wear, deposits, sludge and oxidation under all conditions.

This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ or SL oil is prescribed.

Eurol Sportbike 15W-50 Full Synthetic is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol Sportbike 15W-50 Full Synthetic offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

Eurol Sportbike 15W-50 Full Synthetic has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

At low temperatures Eurol Sportbike Full Synthetic 5W-40 and 15W-50 rapidly provide a solid lubricant film for an optimum protection of the engine at cold starts.

### Performance level

- API SN
- JASO MA
- JASO MA2

### Physical properties

Colour	brown	
Density at 20°C	0.859 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	132.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	18.9 cSt	ASTM D 445
Viscosity Index	162	ASTM D 2270
Viscosity, dynamic (CCS)	4091 cP	ASTM D 5293
Flash point	207 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

Article number E100183  
Version 2.1, 28-10-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.