

Eurol SportScoot 4T 5W-40

4-stroke engine oil, full synthetic lubricant for scooters

Article number E100192 Version 1.0 14/04/2025

Product information

Eurol SportScoot 4T reduces deposits, wear, and oxidation. This product provides better engine protection for four-stroke engines operating under all road conditions.

Eurol SportScoot 4T has been tested for durability and formulated from selected base oils and modern additives, resulting in high performance and properties.

Eurol SportScoot 4T is designed for 4-stroke scooter engines for which manufacturers recommend API SJ / JASO MB specifications.

Eurol SportScoot 4T can be used for various 4-stroke scooters from, among others, Honda, Yamaha, Piaggio, and other specific scooter models with dry clutch type.

The replacement interval of Eurol SportScoot 4T is according to the recommendations of the scooter manufacturers.

Not suitable for mopeds with a wet clutch!

For more information, please contact your local Eurol representative.

Performance level

Recommended for use

API SJ

API SL

JASO MB

Physical properties

| Characteristic | Value/Result | ASTM Standard |
|-------------------------------|--------------|---------------|
| Color | brown | |
| Density at 20°C | 0.84 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C | 86.7 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 14.6 cSt | ASTM D 445 |
| Viscosity Index | 176 | ASTM D 2270 |
| Viscosity, dynamic (CCS) | 5,190 cP | ASTM D 5293 |
| Flash Point | 237 °C | ASTM D 92 |
| Sulfated Ash | 0.7 wt% | ASTM D 874 |
| Pour point | -42 °C | ASTM D 97 |