



Eurol E-HD REEO

Maximum efficiency engine lubricant

Description

Eurol E-HD Range Extender Engine Oil is a premium fully synthetic engine oil specially developed for use in heavy duty equipment range extender engines.

Eurol E-HD Range Extender Engine Oil is formulated to ensure a reliable lubricating film at very low and high temperatures, while reducing friction.

Eurol E-HD Range Extender Engine Oil guarantees the most efficient fuel consumption at any output demand, therefore also increasing the runtime of heavy duty material in the field.

The product has been tested under the toughest conditions, giving the best protection and longest lifespan of the range extender.

Physical properties

Colour	brown	
Density at 20°C	0.844 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	55.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.2 cSt	ASTM D 445
Viscosity Index	174	ASTM D 2270
Viscosity, dynamic (CCS)	5011 cP	ASTM D 5293
Flash point	210 °C	ASTM D 93
Flashpoint COC	240 °C	ASTM D 92

Article number E100310
Version 1.0, 08-03-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.