



Motorcycle oils 4T - Mineral

Eurol Harley 20W-60

Mineral motor oil for Harley Davidson motorcycles

Description

Eurol Harley Davidson oil has especially been developed for Harley Davidson motorcycles. This oil is formulated with selected base stocks and additives, reducing oil consumption to a minimum.

Eurol Harley Davidson oil has been applied for the lubrication of Harley Davidson motorcycles successfully, for many years.

Eurol Harley Davidson withstands heavy shock loads and offers good protection against corrosion and oxidation, so wear is reduced to a minimum. In short: a robust oil for a perfect lubrication which enables the Harley Davidson to last for years.

Performance level

- API SL/CF
- JASO MA
- JASO MA2

Physical properties

Colour	brown	
Density at 20°C	0.875 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	218 cSt	ASTM D 445
Viscosity, kinematic at 100°C	24.3 cSt	ASTM D 445
Viscosity Index	139	ASTM D 2270
Viscosity, dynamic (CCS)	5794 cP	ASTM D 5293
Flash point	200 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

Article number E100380
Version 2.0, 06-03-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.