



Heavy duty diesel engine oils - Semi-synthetic

Eurol Radiax 60

Semi-synthetic engine oil for racing applications

Description

Eurol® Radiax is an ultramodern synthetic motor oil, specially developed for race application. This product is applicable with methanol fuel.

Eurol® Radiax offers first-rate protection under the harshest circumstances by neutralising acidic combustion products, excellent wear protection of all vital parts. This oil has strong dispersing and deterging properties to prevent sludge and deposits.

A very high oil film strength even at high temperatures, combined with an excellent thermal and oxidative stability have resulted in several championships, especially in drag racing.

Performance level

- API CH-4

Physical properties

Colour	brown	
Density at 20°C	0.887 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	180.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	23.1 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	239 cP	ASTM D 5293
Base number	11.7 mg	ASTM D 2896
Flash point	239 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E100910
Version 2.0, 15-01-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.