



Heavy duty diesel engine oils - Semi-synthetic

Eurol Radiax 20W-50

Synthetic motor oil for race applications

Description

Eurol Radiax is an ultramodern synthetic motor oil, specially developed for race applications, and is usable with methanol fuel.

Eurol Radiax offers first-rate protection under the harshest circumstances by neutralising acidic combustion products, excellent wear protection of all vital parts and prevention of sludge and sedimentation.

A very high film strength even at high temperatures, combined with an excellent thermal and oxidative stability have shown results in several championships, especially in drag racing.

Physical properties

Colour	brown	
Density at 20°C	0.891 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	157.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	20.9 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	5460 cP	ASTM D 5293
Base number	8.2 mg	ASTM D 2896
Sulphated ash	1.19 wt%	ASTM D 874
Flash point	192 °C	ASTM D 93
Pour point	-21 °C	ASTM D 97

Article number E100922
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.