



Monograde engine oils - Mineral

Eurol Super Premium SAE 30

Straight mineral motor oil

Description

Eurol Super Premium SAE 30 is a straight mineral motor oil, especially developed for gasoline and diesel engines, operating under favourable working conditions.

Eurol Super Premium SAE 30 is blended from carefully selected solvent refined paraffinic base oils. The product has a low pour point, a high viscosity index and an excellent oxidation stability.

Eurol Super Premium SAE 30 can also be used in systems where there is not placed a load on the oil like in light duty gear boxes and circulation lubrication systems.

Recommended for use

- API SA/CA

Physical properties

Colour	amber	
Density at 20°C	0.875 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	103.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.5 cSt	ASTM D 445
Viscosity Index	98	ASTM D 2270
Flash point	260 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

Article number E101170
Version 1.2, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.