



Heavy duty diesel engine oils - Mineral

# Eurol Monograde 40

Mineral motor oil - Single grade

## Description

Eurol Monograde 40 has specially been developed for light and heavily loaded gasoline - and diesel engines, whether turbo charged or not. The product is also suitable for stationary engines.

Eurol Monograde 40 has strong detergent and dispersant capabilities. This assures the prevention of combustion deposits on pistons, valves and in the combustion chambers.

Eurol Monograde 40 provides optimal protection against wear, corrosion, sludge and foam building. Even at high temperatures the product stays stable and prevents from oil-thickening.

## Performance level

- API SF/CD
- MIL-L-2104B
- MIL-L-46152B

## Recommended for use

- CCMC G2/D1

## Physical properties

Colour	brown	
Density at 20°C	0.889 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	150.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.8 cSt	ASTM D 445
Viscosity Index	98	ASTM D 2270
Base number	10.3 mg	ASTM D 2896
Sulphated ash	1.44 wt%	ASTM D 874
Flash point	273 °C	ASTM D 93
Pour point	-24 °C	ASTM D 97

Article number E101230  
Version 2.1, 03-12-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.