



Tractor oils - S.T.O.U.

# Eurol Altrack 10W-30 STOU

Universal, mineral tractor oil for engine and transmission

## Description

Eurol Altrack 10W-30 STOU is a universal, multi-grade tractor oil (Super Tractor Oil Universal) and is especially developed for application in the engine, transmission and hydraulic system. The product provides a perfect cold start, reduces friction and keeps the engine clean.

Eurol Altrack 10W-30 STOU can be used all year round in tractors equipped with oil immersed disc brakes (so called 'wet brakes'). Because the oil can be applied in the engine, transmission, hydraulic system and wet brakes, it prevents mistakes in the oil selection and it reduces stock.

Eurol Altrack 10W-30 STOU allows an optimum drain interval for an economic use and maintenance. It provides an uncomplicated exchange of hydraulic equipment.

Eurol Altrack 10W-30 STOU offers a perfect protection against corrosion, oxidation and wear, even under extremely high loads, which occur in transmissions. Deterging and dispersing additives keep the oil and the system clean from pollution and impurities.

## Performance level

- API CG-4/SF
- API GL-4
- ACEA E3
- Allison C-4
- MF M1135, MF M1139, MF M1143, MF M1144, MF M1145
- ZF TE ML 06B/06C/06R/07B
- Case MS 1206, MS1209
- MB 228.1
- MB 227.1
- MAN 271
- ZF TE-ML 07D
- MIL-L-2104D
- John Deere J21A
- Ford WSS-M2C159-B/C
- CNH MAT 3505
- CNH MAT 3525
- MIL-L-46152C
- Ford NH 82009201/2/3
- Ford WSS-M2C134-D
- John Deere J20C, J27
- NH 030 C, NH 024 C, NH 410 B, NH 420 A
- Caterpillar TO-2
- FNHA-2-C201

## Recommended for use

- MIL-L-2105

## Physical properties

Colour	brown	
Density at 20°C	0.871 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	68.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.8 cSt	ASTM D 445
Viscosity Index	146	ASTM D 2270
Viscosity, dynamic (CCS)	5571 cP	ASTM D 5293
Flash point	198 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E105075  
Version 4.0, 27-03-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.