



Tractor oils - U.T.T.O.

Eurol Hykrol PST 80

UTTO for agricultural transmissions, clutches, final drives and wet brakes

Description

Eurol Hykrol PST 80 has been specially developed for transmissions of combined bulldozer, tractor and other agricultural devices, fluid clutches, power steering, hydraulic systems and torque converters.

Eurol Hykrol PST 80 has very favourable friction characteristics and is therefore exceptionally suited for "wet brake" systems. It prevents so-called 'stick slip', ensuring smooth shifting and clutching all year long.

Eurol Hykrol PST 80 has a high viscosity index, a very strong oil film and good EP and anti-wear properties. It offers good protection against corrosion, oxidation and foam building. Noise from brakes, final drives and axles is reduced to minimum due to the unique additive technology, combined with adjusted viscometrics.

To benefit optimally from the exceptional properties of this product, mixing with other products should be minimized.

Performance level

- API GL-4
- Allison C-4
- Case MS 1205
- MF M1139
- MF M1135
- Ford WSS-M2C 86B/C
- MF M1127A
- Caterpillar TO-2

Recommended for use

- CNH MAT 3540

Physical properties

Colour	brown	
Density at 20°C	0.876 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	79.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.3 cSt	ASTM D 445
Viscosity Index	133	ASTM D 2270
Flash point	193 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Article number E105822
Version 3.0, 01-03-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.