



Tractor oils - U.T.T.O.

## Eurol Hykrol CT Fluid

UTTO for agricultural transmissions, clutches, final drives and wet brakes

### Description

Eurol Hykrol CT Fluid is an oil, especially developed for transmissions and hydraulic, oil-cooled brake and clutch systems, of agricultural, home gardening and industrial tractors. Because of the low pour point, this oil is especially suitable for cold climate conditions.

Eurol Hykrol CT Fluid has very favourable friction characteristics and therefore is exceptionally suitable for 'wet brake' applications. It prevents from so called 'stick-slip' and the accompanied noise, all year round.

Eurol Hykrol CT Fluid is suitable for modern disc brake materials. It also offers ample protection against wear, oxidation, corrosion and foam building and ensures a long life-time.

### Performance level

- API GL-4
- Case MS 1207
- CNH MAT 3505
- ZF TE-ML 03F
- Case MS 1210
- Ford WSS-M2C41-B
- Ford WSS-M2C48-C
- IH B -6
- John Deere J20D
- Caterpillar TO-2

### Physical properties

|                               |            |             |
|-------------------------------|------------|-------------|
| Colour                        | brown      |             |
| Density at 20°C               | 0.863 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C  | 41.2 cSt   | ASTM D 445  |
| Viscosity, kinematic at 100°C | 7.3 cSt    | ASTM D 445  |
| Viscosity Index               | 143        | ASTM D 2270 |
| Flash point                   | 197 °C     | ASTM D 93   |
| Pour point                    | -33 °C     | ASTM D 97   |

Article number E105825  
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.