

Eurol Hykrol CT Fluid

UTTO for agricultural transmissions, clutches, final drives and wet brakes

Article number E105825 Version 1.0 14/04/2025

Product information

Eurol Hykrol CT Fluid is an oil specifically developed for transmissions, hydraulic, and oil-cooled brake and clutch systems of agricultural, garden, and industrial tractors. Due to its low pour point, this oil is particularly suitable for winter applications.

Eurol Hykrol CT Fluid has a very favorable friction characteristic and is therefore ideally suited for wet brakes systems. It prevents the so-called 'stick slip' throughout the year, and the associated noise.

Eurol Hykrol CT Fluid is suitable for modern disc brake materials. It also provides ample protection against wear, oxidation, corrosion, and foaming and has a long lifespan.

Performance level

- API GL-4
- Case MS 1207
- Case MS 1210
- Caterpillar TO-2
- **CNH MAT 3505**
- Ford WSS-M2C41-B
- Ford WSS-M2C48-C
- IH B -6
- John Deere J20D
- ZF TE-ML 03F

Physical properties

| Characteristic | Value/Result | ASTM Standard |
|-------------------------------|--------------|---------------|
| Color | brown | |
| Density at 20°C | 0.86 kg/l | ASTM D 4052 |
| Viscosity, kinematic at 40°C | 41.2 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 7.3 cSt | ASTM D 445 |
| Viscosity Index | 143 | ASTM D 2270 |
| Flash Point | 197 °C | ASTM D 92 |
| Pour point | -33 °C | ASTM D 97 |