



Technical fluids - Front fork oils

Eurol Front Fork Oil SAE 30

Universal fork oils

Description

Eurol Front Fork Oil SAE 30 is blended from carefully selected paraffinic base oils with a low pour point and a high viscosity index.

Eurol Front Fork Oil SAE 30 is inhibited with very effective additives, ensuring an exceptional hydraulic springing and shock absorbing action. Scuffing and wear are reduced to a minimum, while a smooth movement is guaranteed. Besides, this oil offers good protection against foam-building and corrosion. Seals are not affected by this product.

Eurol Front Fork Oil SAE 30 has a high thermal and oxidation stability and can be applied in a broad temperature range. Due to the stable viscosity index improvers, the viscosity will stay in grade over a very long time.

Physical properties

Colour	red	
Density at 20°C	0.872 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	67 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.6 cSt	ASTM D 445
Viscosity Index	125	ASTM D 2270
Flash point	198 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E107030
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.