



Eurol Front Fork Oil SAE 2,5

Universal fork oils

Description

Eurol Front Fork Oil SAE 2,5 is blended from carefully selected paraffinic base oils with a low pour point and a high viscosity index.

Eurol Front Fork Oil SAE 2,5 is inhibited with very effective additives, ensuring an exceptional hydraulic springing and shock absorbing action. Scuffing and wear are reduced to a minimum, while a smooth movement is guaranteed. Besides, this oil offers good protection against foam-building and corrosion. Seals are not affected by this product.

Eurol Front Fork Oil SAE 2,5 has a high thermal and oxidation stability and can be applied in a broad temperature range. Due to the stable viscosity index improvers, the viscosity will stay in grade over a very long time.

Physical properties

Colour	Yellow	
Density at 20°C	0.823 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	6.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	2.5 cSt	ASTM D 445
Viscosity Index	272	ASTM D 2270
Flash point	119 °C	ASTM D 93
Pour point	-54 °C	ASTM D 97

Article number E107978
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.