



Transmission oils - Fully Synthetic

Eurol HPX VC 75W-80

Fully synthetic lubricant for Voith Retarder applications

Description

Eurol HPX VC 75W-80 is a fully-synthetic (PAO) lubricant developed specially for Voith retarders in commercial vehicles and busses.

Eurol HPX VC 75W-80 has excellent viscosity-temperature properties at very low temperatures.

Eurol HPX VC 75W-80 provides protection against mechanical and thermal loads.

Eurol HPX VC 75W-80 is especially suited for drain intervals up to a maximum of 300.000 km depending on application and according to manufacturer's instructions. Extended long oil drain intervals reduce maintenance costs and increase economy.

Eurol HPX VC 75W-80 is recommended for use where one of the OEM specifications Voith Retarder Category C, MAN 341 Typ VR and MB 235.29 is required. Suitable for retarders of Renault, Volvo, MAN and Mercedes-Benz requiring such quality oils.

Please consider the OEM's/heavy duty vehicles instruction manual!

Approved

- Voith Class C

Performance level

- MAN 341 TYPE VR
- MB 235.29

Physical properties

Colour	brown	
Density at 20°C	0.842 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	50.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.9 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Base number	4.0 mg	ASTM D 2896
Flash point	235 °C	ASTM D 93
Pour point	-50 °C	ASTM D 97

Article number E110070
Version 6.0, 06-10-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.