



POWERING
PERFORMANCE

PRODUCT DATA SHEET

Eurol Fultrax 75W-90 LS

Fully synthetic "limited-slip" gear oil

Article number E110079 Version 1.0 14/05/2025

Produktinformationen

The Eurol Fultrax 75W-90 LS is a high-quality fully synthetic transmission oil, designed to meet the stringent demands of heavily loaded transmission systems. This oil contains a 'Limited-Slip' additive making it particularly suitable for vehicles with plate clutch 'Limited-Slip' differentials, as often used in modern cars, trucks, tractors, and earth-moving machines.

The product is formulated for use in hypoid gears, hub reductions, and differentials, both with and without plate clutches. Due to its very high viscosity index and excellent flow properties at low temperatures, Eurol Fultrax 75W-90 LS remains efficient under heavy operating conditions. The 'stay in grade' character of this oil ensures that it retains its properties even under extreme conditions.

The advanced additive technology in Eurol Fultrax 75W-90 LS offers superior protection against thermal oxidation, helps reduce corrosion and wear, and does not negatively affect the vehicle's seals. Moreover, the special friction modifiers in this oil contain components that help reduce noise during cornering, a common issue in 'Limited-Slip' applications.

This makes Eurol Fultrax 75W-90 LS an ideal choice for a wide range of vehicles and machines, where the oil helps to extend the lifespan and performance of the transmission system.

For more information, consult the manual or find oil recommendations on our product advisor at www.eurol.com.

Performance level

- API GL-5 LS
- MAN 342 M-2
- Volvo STD 1273,1
- ZF TE-ML 05A, 7A, 12E, 16B,C,D, 17B, 19B, 21A

Recommended for use

- Dexron LS gear
- Fiat 9.55550-DA4/Fiat 9.55550 -DA9
- GM 9986226
- VW G 052 196

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	Yellow	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	80.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.2 cSt	ASTM D 445
Viscosity Index	200	ASTM D 2270
Pour point	-42 °C	ASTM D 97

Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.