



# Eurol Fultrax 75W-90 LS

Fully synthetic "limited-slip" gear oil

## Description

The Eurol Fultrax 75W-90 LS is a high-quality fully synthetic transmission oil, designed to meet the stringent requirements of heavily loaded transmission systems. This oil contains a 'Limited-Slip' additive, making it particularly suitable for vehicles with clutch-type limited slip differentials, commonly used in modern cars, trucks, tractors, and construction machinery.

The product is formulated for use in hypoid transmissions, hub reductions, and differentials, both with and without limited slip function. Due to its very high viscosity index and excellent flow properties at low temperatures, Eurol Fultrax 75W-90 LS remains efficient under heavy operating conditions. The 'stay in grade' character of this oil ensures that it retains its properties even under extreme conditions.

The advanced additive technology in Eurol Fultrax 75W-90 LS offers superior protection against thermal oxidation, helps reduce corrosion and wear, and does not negatively affect seals. Moreover, the special friction modifiers in this oil contain components that contribute to reducing noise when taking turns, a common issue with limited slip applications.

This makes Eurol Fultrax 75W-90 LS an ideal choice for a wide range of vehicles and machines, helping to extend the life and performance of the transmission system.

For more information, refer to the manual or seek oil recommendations on our product advisor at [www.eurol.com](http://www.eurol.com).

## Performance level

- API GL-5 LS
- MAN 342 M-2
- Volvo STD 1273,1
- ZF TE-ML 05A, 7A, 12E, 16B,C,D, 17B, 19B, 21A

## Recommended for use

- VW G 052 196
- Fiat 9.55550-DA4/Fiat 9.55550-DA9
- Dexron LS gear
- GM 9986226

## Physical properties

Colour	Yellow	
Density at 20°C	0.865 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	80.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.2 cSt	ASTM D 445
Viscosity Index	200	ASTM D 2270
Flashpoint COC	245 °C	ASTM D 92
Pour point	-42 °C	ASTM D 97

Article number E110079  
Version 1.0, 18-04-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.