



Transmission oils - Fully Synthetic

# **Eurol HPX MB 75W-85 GL-5**

Full synthetic transmission oil for manual gearboxes and differentials

### **Description**

Eurol HPX MB 75W-85 GL-5 is a high-quality full synthetic transmission oil, designed for manual gearboxes and differentials where SAE 75W-85 oil with API: GL-5 specification is recommended. This oil is particularly suitable for the differentials of Mercedes-Benz vehicles, which require specifications DTFR 12B120 (MB 235.31) and MB 235.33.

Thanks to an exceptionally low pour point and high viscosity index, Eurol HPX MB 75W-85 GL-5 guarantees smooth shifting under all conditions, both at high and low temperatures. The combination of advanced additives and synthetic base oils ensures excellent stability and effective protection against wear.

Eurol HPX MB 75W-85 GL-5 is a fuel-saving transmission oil that meets the demands of modern transmission systems with synchromesh rings, providing superior performance in demanding applications.

#### Benefits:

- · Supports smooth shifting in extreme temperatures
- $\bullet$  Compatible with Mercedes-Benz specifications DTFR 12B120 (MB 235.31) and MB 235.33
- Fuel-saving, reduces component wear
- Promotes a long lifespan of transmission systems

For more information, consult the manual or use the product advisor at www.eurol.com for advice on the right transmission oil for your vehicle.

#### Performance level

- DTFR 12B120 (MB 235.31)
- MB 235.33
- API GL-5
- Arvin Meritor O-94
- SAE J2360
- DETROIT DIESEL DFS93K219.03
- Scania STO 1:0

### Recommended for use

- ZF TE-ML 04G
- ZF TE-ML 07A
- ZF TE-ML 08

## **Physical properties**

i ilyaicai properties		
Colour	Yellow	
Density at 20°C	0.853 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	70.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12 cSt	ASTM D 445
Viscosity Index	167	ASTM D 2270
Flash point	200 °C	ASTM D 92
Pour point	-42 °C	ASTM D 97

Article number E110607 Version 1.0, 19-09-2024