



Transmission oils - Mineral

Eurol MPG EP 85W-140 GL4

Mineral transmission oil for manual gearboxes and final drives

Description

Eurol MPG SAE 85W-140 GL4 is formulated from paraffinic base stocks and additives, including EP (Extreme Pressure) additives according to the phosphor/sulphur technology.

Eurol MPG SAE 85W-140 GL4 is recommended for many types of manual gearboxes and final drives in passenger cars, buses and commercial vehicles and for which an API GL-4 transmission oil is prescribed.

Eurol MPG SAE 85W-140 GL4 also contains additives preventing from corrosion, oxidation and foam building. By this a smooth shifting is guaranteed for a long time.

Seals are not affected by the Eurol MPG SAE 85W-140 GL4 and the product prevents from undesired deposits.

Performance level

- API GL-4
- MIL-L-2105

Physical properties

Colour	brown	
Density at 20°C	0.897 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	371 cSt	ASTM D 445
Viscosity, kinematic at 100°C	26.4 cSt	ASTM D 445
Viscosity Index	95	ASTM D 2270
Flash point	200 °C	ASTM D 93
Pour point	-18 °C	ASTM D 97

Article number E110610
Version 1.0, 04-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.