



POWERING  
PERFORMANCE

# Eurol ATF 1200

Automatic transmission fluid for light and medium-duty vehicles

Article number E113651 Version 1.0 15/04/2025

## Product information

Eurol ATF 1200 is a fully synthetic automatic transmission fluid for passenger cars and light commercial vehicles.

Eurol ATF 1200 offers excellent lubrication properties, ensuring comfortable shifting behavior under all operating temperatures. The superior oxidation stability of Eurol ATF 1200 guarantees a reliable product throughout the entire drain interval.

Eurol ATF 1200 can be used in traditional automatic transmissions mainly manufactured in Europe and Asia, developed before 2010. Please consult the oil advisor on the Eurol website for specific recommendations.

## Recommended for use

- ATF LA-2634
- ATF LT 71141
- ATF RED 1K
- Chrysler MS 7176E (ATF +3)
- ETL 7045E
- ETL 8072B
- Ford Mercon
- Ford WSS-M2C138-CJ
- Ford WSS-M2C166-H
- Ford WSS-M2C922-A1
- GM Dexron IID
- GM Dexron IIIG
- GM Dexron IIH
- Honda Z1 (except CVT)
- Hyundai/Mitsubishi SP,SP-II,SP-III,DiaQueenJ2
- Idemitsu K17
- Isuzu besco ATF-II,ATF-III
- JASO M 315 1A
- JWS 3309/3314/3317
- Mazda M-III, M-5
- Nissan Matic D, J, K
- Subaru ATF
- Toyota/Lexus T, T-II, T-III, T-IV
- Volvo 1161540
- VW G 052 055
- VW G 052 162
- VW G 052 990
- VW G 055 025

**Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com**

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.



POWERING  
PERFORMANCE

# Eurol ATF 1200

Automatic transmission fluid for light and medium-duty vehicles

Article number E113651 Version 1.0 15/04/2025

## Physical properties

Characteristic	Value/Result	ASTM Standard
Color	red	
Density at 20°C	0.84 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	33.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.5 cSt	ASTM D 445
Viscosity Index	200	ASTM D 2270
Flash Point	197 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97

**Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com**

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.