

Eurol ATF III F

Mineral automatic transmission fluid Dexron III F

Article number E113659 Version 2.0 15/04/2025

Product information

Eurol ATF III F is a mineral automatic transmission oil specifically developed for new (post-1995) and older (automatic) transmissions of GM and Ford, as well as many other brands. Additionally, it is suitable for power steering systems, some hydraulic systems, and rotary air compressors where excellent low-temperature fluidity is required.

Eurol ATF III F has a very high viscosity index and offers resistance to corrosion and foaming. Moreover, it has good anti-oxidation and anti-wear properties.

Eurol ATF III F has an extremely low pour point, ensuring smooth shifting after a cold start. This ATF does not affect sealing materials.

Performance level

- Allison C-4
- Caterpillar TO-2
- Dexron III F
- Ford Mercon
- ZF TE-ML 04D
- ZF TE-ML 14A

Recommended for use

- MAN 339 Type V2
- MAN 339 Z-2
- Volvo 97341

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	red	
Density at 20°C	0.86 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	35.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.3 cSt	ASTM D 445
Viscosity Index	175	ASTM D 2270
Flash Point	250 °C	ASTM D 92
Pour point	-48 °C	ASTM D 97