



Automatic transmission fluids - Mineral

Eurol ATF III F

Mineral automatic transmission fluid Dexron III F

Description

Eurol ATF III F is a mineral based automatic transmission fluid, especially developed for new (after 1995) and older (automatic) transmissions, build by GM, Ford and many other manufactures. It is also suitable for power steering systems, some hydraulic systems and for rotary air compressors where an excellent low temperature fluidity is required.

Eurol ATF III F has a very high viscosity index and offers resistance against corrosion and foam building. The product also has good anti oxidation and anti wear properties.

Eurol ATF III F has an extremely low pour point which allows easy gear shifting at cold starts. Seals are not affected by this ATF

Approved

- ZF TE-ML 04D/14A
- ZF registration no.000387

Performance level

- Allison C-4
- Dexron III F
- Ford Mercon
- Caterpillar TO-2

Recommended for use

- MAN 339 Type V2
- MAN 339 Z-2
- Volvo 97341

Physical properties

Colour	red	
Density at 20°C	0.859 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	37.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.4 cSt	ASTM D 445
Viscosity Index	169	ASTM D 2270
Flash point	186 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

Article number E113659
Version 1.1, 18-09-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.