



Automatic transmission fluids

Eurol ATF 6800 ULV

Full synthetic transmission oil for automatic transmissions requiring ultra low viscosity

Description

Eurol ATF 6800 ULV is a high-quality full synthetic transmission oil, specifically developed for automatic transmissions that require an ultra low viscosity ATF, such as Ford Mercon ULV and GM Dexron ULV. Due to its extremely low viscosity, this oil contributes to significant fuel savings and a reduction in CO₂ emissions compared to conventional ATFs.

With a high viscosity index and low pour point, this oil performs effectively across a wide temperature range, ensuring smooth shifting under all operating conditions with minimal friction. The product offers excellent oxidation resistance and high thermal stability, providing optimal wear protection throughout the entire service interval.

The combination of premium synthetic base oils and advanced additives ensures that Eurol ATF 6800 ULV maintains consistent and reliable quality, which is crucial for the long-lasting and efficient operation of transmissions.

Benefits:

- Supports fuel savings and reduces CO₂ emissions
- Smooth shifting across a wide temperature range
- Excellent oxidation resistance and thermal stability
- Provides superior wear protection over the entire service interval

For more information, consult the manual or use the product advisor at www.eurol.com for advice on the right transmission oil for your vehicle.

Recommended for use

- Aisin Warner AW-2
- BMW 83 22 2 413 477 (ATF 7)
- Ford Mercon ULV
- Ford XT-12-ULV
- GM Dexron ULV
- Mazda ATF A7
- MB 236.15/MB 236.16/MB 236.17
- Nissan Matic P
- PSA 16 350 560 80
- Volvo 31 492 172/31 492 173
- VW/Audi G 053 001
- VW/Audi G 060 540

Physical properties

Colour	Yellow	
Density at 20°C	0.838 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	21.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	4.7 cSt	ASTM D 445
Viscosity Index	143	ASTM D 2270
Flash point	210 °C	ASTM D 92
Pour point	-54 °C	ASTM D 97

Article number E113671
Version 1.0, 19-09-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.