



Automatic transmission fluids - Mineral

## Eurol Powersteering fluid A

Mineral power steering fluid / hydraulic oil and A.T.F.

### Description

Eurol Powersteering Fluid A is a power steering fluid, that can also successfully be used as an hydraulic oil.

Eurol Powersteering Fluid A has a high thermal and oxidation stability and offers an exceptional good protection against corrosion, wear and foam building. This guarantees a long and uncomplicated life time of the oil and the equipment.

Eurol Powersteering Fluid A has a low pour point, enabling smooth shifting and steering at low temperatures.

### Performance level

- ATF A suffix A
- ATF Dexron B

### Recommended for use

- DTFR 13C120 (MB 236.2)
- Ford WSS-M2C41-A/B
- MAN 339 Type A
- Volvo 97325

### Physical properties

Colour	red	
Density at 20°C	0.852 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	34.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7 cSt	ASTM D 445
Viscosity Index	171	ASTM D 2270
Flash point	197 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E113680  
Version 1.3, 27-11-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.