



Technical fluids - Powersteering

Eurol Powersteering fluid D

Mineral power steering fluid / hydraulic oil and A.T.F.

Description

Eurol Powersteering Fluid D is a mineral automatic transmission fluid (Dexron IID level) which can be used successfully as power steering fluid and as an hydraulic oil.

Eurol Powersteering Fluid D has a high thermal and oxidation stability and offers an extremely good protection against corrosion, wear and foam building. This guarantees a long life cycle for the oil and the equipment, without complications.

Eurol Powersteering Fluid D has a very low pour point, enabling smooth shifting and steering at low temperatures.

Recommended for use

- Allison C-4
- Dexron IID
- Ford ESP-M2C166-H
- Ford M2C138-CJ
- Ford Mercon
- Voith 55.6335.xx (G607)
- Caterpillar TO-2

Physical properties

Colour	red	
Density at 20°C	0.865 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	38.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.6 cSt	ASTM D 445
Viscosity Index	170	ASTM D 2270
Flash point	188 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Article number E113685
Version 2.0, 16-03-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.