



Quality is in our nature

Industrial oils - Vacuum pump

Eurol Vacuumolie ISO-VG 46

Mineral vacuum pump oil

Description

Eurol Vacuum pump Oil ISO-VG 46 is an oil with a very good oxidation stability. Therefore, this oil is perfectly suitable for application in vacuum pumps, operating under heavy duty working conditions.

Eurol Vacuum pump Oil ISO-VG 46 is blended from solvent refined paraffinic base oils with low vapour pressure. A minimum amount of additives provides sufficient protection against wear, rust and corrosion, while water and vapour are rapidly separated.

Eurol Vacuum pump Oil ISO-VG 46 has a naturally high viscosity index, which prevents inconvenient viscosity changes, caused by temperature differences.

Physical properties

Colour	Amber	
Density at 20°C	0.86 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	45.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7 cSt	ASTM D 445
Viscosity Index	111	ASTM D 2270
Flash point	210 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

Available in 5L - 20L - 60L

E122572
Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com