



Quality is in our nature

Industrial oils - Chain

Eurol Chainsaw Oil AK 100

Strong tenacious, mineral chainsaw oil for chains and guide bars

Description

Eurol Chainsaw Oil AK 100 is formulated from highly refined mineral base oils and specially selected additives providing a high film strength and tackiness.

Eurol Chainsaw Oil AK 100 is recommended for both engine driven, as well as for electrically driven chainsaws.

Eurol Chainsaw Oil AK 100 penetrates deeply between links and bushes, adheres without dripping or flinging off and prevents dirt, sand and/or dust accumulation. Furthermore, the chain is well protected from corrosion.

Physical properties

| | | |
|-------------------------------|------------|-------------|
| Colour | Brown | |
| Density at 20°C | 0.877 kg/l | ASTM D 1298 |
| Viscosity, kinematic at 40°C | 102.3 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 11.2 cSt | ASTM D 445 |
| Viscosity Index | 95 | ASTM D 2270 |
| Flash point | 233 °C | ASTM D 93 |
| Pour point | -12 °C | ASTM D 97 |

E125451

Version 2.0, 02-05-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com