



Transmission oils - Mineral

Eurol Gear Oil EP

transmission oil with EP performance

Description

Performance level

- API GL-5
- MIL-L-2105 B/C/D

Recommended for use

- Mack GO-G

Physical properties

Colour	brown	
Density at 20°C	0.883 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	136.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.1 cSt	ASTM D 445
Viscosity Index	100	ASTM D 2270
Flash point	244 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

Article number E126207
Version 1.3, 23-01-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.