



Scooter oils 2T - Mineral

Eurol Nautic L. Sup Outb. 2T

Mineral 2-stroke oil for lubrication of modern outboard motors

Description

Eurol Nautic Line Super Outboard 2T is a self-mixing 2-stroke oil, especially developed for the lubrication of modern outboard motors and is suitable for both pre-mix systems, as well for oil injection systems.

Eurol Nautic Line Super Outboard 2T is formulated with carefully selected base oils and special additives, providing a long-lasting protection. Due to a very strong lubricating film, a perfect lubrication is guaranteed, even at high temperatures.

Eurol Nautic Line Super Outboard 2T effectively protects the vital engine parts from wear and corrosion and prevents from deposits on pistons and in the exhaust system. With this oil CO₂ emission is strongly reduced.

"Mixing ratio:

Maximum 1:100, according to manufacturers instructions"

Performance level

- NMMA TC-W3

Physical properties

Colour	Blue	
Density at 20°C	0.869 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	42.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.8 cSt	ASTM D 445
Viscosity Index	116	ASTM D 2270
Base number	8.0 mg	ASTM D 2896
Flash point	134 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

Article number E128430
Version 1.1, 24-08-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.