



Automatic transmission fluids

# Eurol Carbon Neutral ATF 6700

Effortless CO<sub>2</sub>-footprint reduction

## Description

Eurol Carbon Neutral ATF 6700 is the CO<sub>2</sub>-neutral, more sustainable choice compared to standard low-viscosity automatic transmission fluids. This fully synthetic ATF oil is manufactured with more environmentally conscious components and is largely (at least 80%) derived from renewable sources.

Eurol Carbon Neutral ATF 6700 guarantees comparable quality and performance to standard recommended ATF oils. This makes switching to this sustainable automatic transmission fluid straightforward.

Eurol Carbon Neutral ATF 6700 aligns with programs aimed at CO<sub>2</sub>-reduction, including Lean and Green initiatives.

## Benefits

- Sustainable, environmentally conscious choice
- Smooth shifting under all conditions
- Comparable quality and performance to standard ATF oils
- Fits into CO<sub>2</sub>-reduction programs

## Recommended for use

- Aisin Warner AW-1
- Bentley Oil PY112995PA
- CHRYSLER 68157995AA
- DSI H 6-SPEED TRANSMISSION (AT 3292)
- Fiat 9.55550-AV2
- Fiat 9.55550-AV5
- Ford WSS-M2C924-A
- GM Dexron VI
- Honda ATF DW-1
- HYUNDAI NWS-9638
- Hyundai SP IV, SPH-IV
- JAGUAR 02JDE26444
- Jaguar Fluid 8432
- JWS 3324 (ATF WS)
- LAND ROVER LR023288
- Land Rover TYK 500050
- M-1375.4
- Maserati 231603
- Mazda FZ
- MB 236.12
- MB 236.41
- Mercon LV
- Mercon SP
- Mitsubishi SP-IV & ATF J-2
- Nissan Matic S
- SAAB 93 165 147
- Toyota Type WS (JWS 3324)
- VW G 055 005
- VW G 055 162
- VW G 055 540
- VW G 060 162
- ZF Lifeguardfluid8

## Physical properties

Colour	yellow to brown	
Density at 20°C	0.827 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	28.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6 cSt	ASTM D 445
Viscosity Index	166	ASTM D 2270
Flash point	200 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97

Article number E173653  
Version 1.2, 02-09-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.