



Technical fluids - Rust preventives

Eurol UBC Black

Spray-equipment, black, corrosion protecting

Description

Eurol UBC Black is a durable, fast drying and anti-corrosion coating based on bitumen. The coating offers a lasting protection to the underbody of cars, trailers, caravans, storage tanks, boats and on repaired parts.

Eurol UBC Black is soundproof and has an excellent resistance against rust and the oxidating action of chemicals.

Eurol UBC Black is applied by a suction gun or a drum suction gun. Do not apply more than 1-3 mm. Use in a well ventilated area. The product can be diluted with solvent. The surfaces to be treated must be clean, dry, rust-, dust- and grease free.

Spray the surface with Eurol Non-Airless until the desired layer thickness is reached. If thicker layers are wanted, it is to be recommended to dry the layers in between. Contaminated surfaces and filthy equipment can be cleaned in "fresh" condition with solvent. Shake before use.

Physical properties

Colour	Black
Flash point	29 °C ASTM D 93

Article number E201120
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.