

Technical fluids - Rust preventives

Eurol ML Injectie Wax

For airless spray equipment, corrosion protecting, for internal coatings

Description

Eurol ML Injection Wax is a thin, water-repellent, durable, white/transparent anti-corrosion product. It can be used especially for hollow parts like chassis beams, doors, door pillars, flanges, welded seams, decorative strips and chrome parts.

Eurol ML Injection Wax is has been formulated from mineral oils, paraffinic waxes and inhibitors. It has anti-corrosion properties and will not affect rubber or lacquer. Eurol ML Injection Wax protects over a prolonged time, even in a salty environment (e.g. shipping transport).

Besides the anti-corrosion properties, Eurol ML Injection Wax also has excellent water repellent and penetrating properties. After drying, a slightly tacky, transparent, waxy film remains. This film is resistant to high temperatures as are found in engine compartments.

Eurol ML Injection Wax can be sprayed easily and shows a capillary movement. By this, every spot is covered. It can be applied by spray gun or airless spray equipment.

Physical properties

| Colour | light brown | |
|-------------|-------------|-----------|
| Flash point | 36 °C | ASTM D 93 |

Article number E201201 Version 1.1, 04-12-2017

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.