



Technical fluids - Battery fluids

Eurol Battery Acid

For top-up all types of batteries

Description

Eurol Battery Acid contains 37% sulphuric acid and is suitable for every brand of battery. For topping-up batteries, always use demineralised water.

Lead batteries are filled with sulphuric acid, density 1.28 kg/l.

Warnings:

This product is corrosive/biting

Never add water to acid (always add acid to the water).

This acid can cause burns on the skin and affects many materials. In case of skin contact, immediately rinse with plenty of water!

In case of eye contact, immediately rinse with plenty of water and consult a doctor!

Spilled battery acid is to be flushed away with plenty of water, alternatively neutralize with caustic soda.

During charging a battery, explosive hydrogen gas will be formed. A small spark is sufficient to make the battery explode.

Place the battery in a well ventilated area

Avoid sparks and open fire close to the battery.

Physical properties

Colour	Colourless	
Density at 20°C	1.28 kg/l	ASTM D 4052
pH	1	

Article number E301300
Version 1.0, 26-08-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.