



Eurol Delec Fluid 70-X

Aromatic-free solvent

Description

Eurol Delec Fluid 70-X is an aromatic-free and emulsifiable solvent which is very suitable for degreasing surfaces and parts.

Preserving oils, cutting oils, lubricating oils and greases are easily removed by Eurol Delec Fluid 70-X, as well as dust, dirt and small (metal) contaminations.

Eurol Delec Fluid 70-X can be used in various degreasing processes like spraying, dipping, or ultrasonic cleaning. It can easily be removed by compressed air. Operating temperatures up to 60°C are safe.

Eurol Delec Fluid 70-X should be used undiluted and can be applied by immersion or by low-pressure spray gun. Allow a 5 to 10 minute acting time and then rinse with warm or cold water and/or blow dry with compressed air.

Physical properties

Colour	red	
Density at 20°C	0.802 kg/l	ASTM D 4052
Flash point	63 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E302150
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.