



Eurol Demoulding Oil

Description

Eurol Demoulding oil is a water emulsifiable metalworking fluid concentrate for general machining of cast iron, alloy as well as unalloy steel, aluminium and yellow metal. You can use the Eurol Demoulding oils as a concrete release agent.

Thanks to its specially chosen top grade emulsifier system and excellent lubricity additives, the product is highly versatile.

Physical properties

Colour	Brownish	
Density at 20°C	0.903 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	49.2 cSt	ASTM D 445
Flash point	100 °C	ASTM D 93

Article number E401470
Version 1.1, 22-09-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.