



Coolants & screenwash

Eurol Antifreeze BS 6580

Meets BS 6580 standard, suitable for open and closed cooling systems

Description

Eurol Antifreeze is recommended for all cooling systems of combustion engines (both LPG, gasoline and diesel) and other heat transfer systems like central heating installations. It is a homogeneous, stable product, based on mono-ethylene-glycol and formulated according to European car manufacturers instructions.

Eurol Antifreeze contains additives, protecting against corrosion and foam-building. Due to the high reserve alkalinity, the cooling system has a long-term protection against corrosion.

Eurol Antifreeze offers the best protection when applied in a concentration of 25 up to 50 vol.%. Concentrations above 65 % should be avoided because of a decreasing frost protection.

Eurol Antifreeze is completely safe for rubbers, plastics, metals, aluminum and alloys. The product is free of nitrites, amines and phosphate.

Vol% in water : 25 30 33 40 50

Frostprotection (°C) : -11 -16 -18 -26 -37

Performance level

- BS 6580
- ASTM D3306

Physical properties

Colour	Blue	
Density at 20°C	1.109 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93

Article number E503150
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.