

Eurol Antifreeze MPG

Nontoxic biodegradable antifreeze

Description

Eurol Antifreeze MPG is recommended in all heat exchanging cooling systems, such as e.g. central heating circuits with water circulation and for air conditioning. It is a homogenous, stable product based on monopropylene glycol.

Eurol Antifreeze MPG is not poisonous and contains additives that offer protection against corrosion and foaming. It protects metals such as steel, copper, brass, aluminium, solder against corrosion.

Eurol Antifreeze MPG offers the best corrosion protection when it is used in concentrations of 25 to 60 volume% in water. Concentrations higher than 65% are not advised, especially since the frost protection then decreases.

Eurol Antifreeze MPG is completely safe for rubbers, plastics, metals and aluminium or alloys. It is free of nitrite, amine and phosphate. Coolants & screenwash

Performance level

- BS 6580
- ASTM D3306

Physical properties

Colour	Colourless	
Density at 20°C	1.04 kg/l	ASTM D 4052
Flash point	100 °C	ASTM D 93
Pour point	-15 °C	ASTM D 97

Article number E503165 Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.