



Coolants & screenwash - Cooling fluids

# Eurol Coolant -36°C G11

Long-Life Coolant

## Description

Eurol Coolant -36 G11 is recommended for use in cooling systems of liquid cooled automotive and industrial internal combustion engines.

Eurol Coolant -36 G11 protects car, truck and bus engines of both ferrous and aluminium construction against corrosion and frost damage. It contains a blend of inhibitors designed to give a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads and water pumps. Eurol Coolant -36 G11 provides year-round frost and corrosion protection.

Dilution of the coolant with water is not recommended.

Free of nitrite, amine and phosphate.

## Performance level

- VW TL-774 C (G11)
- BS 6580
- ASTM D3306 / D4656 / D4985
- AFNOR NFR 15-601
- MB 326.2
- MB 326.0
- MAN 324 Typ NF
- MTU MTL 5048
- Fiat 9.55523
- BMW GS 94000 / N 600 69.0

## Recommended for use

- SAE J1034
- NATO S-759
- JASO M325

## Physical properties

Colour	Green	
Density at 20°C	1.075 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.3	

Article number E504010  
Version 1.2, 28-12-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.