



Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C GLX-AV

Coolant Phosphated Organic Additive Technology P-OAT

Description

Eurol Coolant -36°C GLX-AV is a cooling and heat transfer fluid that has been specially developed for cooling systems according to the modern requirements of most Japanese and Korean car manufacturers.

Eurol Coolant -36°C GLX-AV can be used in cooling systems of both petrol and diesel engines made of cast iron, aluminium or a combination of these two metals. Copper alloys are also not affected by this product. This coolant prevents formation of deposits, corrosion, foaming, sludge and leakage. It does not attack rubbers, plastics, metals and alloys.

Eurol Coolant -36°C GLX-AV is based on OAT technology, with phosphate compounds added, also referred to as a P-OAT (Phosphated Organic Additive Technology) coolant. This product does not contain silicates, amines, nitrites and amines and offers improved hard water stability. Due to this special composition, this product offers optimal heat transfer without creating deposits. This coolant provides a permanent guaranteed frost protection of -36 ° C and must be used undiluted.

Eurol Coolant -36°C GLX-AV can be mixed with all types of engine coolants based on (mono) ethylene glycol. However, mixing with other types of engine coolants shortens the drain interval. It is therefore recommended to keep mixing with other types of coolant to a minimum.

Consult the Eurol Oil Advisor on eurol.com to determine which coolant is suitable for your vehicle.

Performance level

- ASTM D3306
- ASTM D6210
- Ford WSS-M97B57-A1
- Honda Type 2
- JIS K2234
- Mazda FL22

Recommended for use

- Mitsubishi
- Subaru
- Suzuki

Physical properties

Colour	Blue	
Density at 20°C	1.072 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177

Article number E504030
Version 1.1, 16-08-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.